


REGULAR V2 MINI CUT

MiniCut strip with latest LED generation
Ruban LED de dernière génération mini sécabilité
A4159



Temperature de couleur CCT
1800K - 2100K - 2400K - 2700K - 3000K - 3500K - 4000K - 5000K - 6000K

Precision de couleur & IRC Color consistency & CRI
OneBinOnly I >90 (>95 on request)

Rendement lumineux Luminous Efficacy (@4000K)
152 lm/w


Puissance & nombre de led Power & number of Led
19 w/m & 120 leds/m

Coupe Cutting unit
8.33 mm

Dimensions Dimensions
5000 x 10 x 1.2 mm

Tension d'alimentation & Classe isolation Input voltage & Class
24Vdc I class III

Température d'utilisation Ambient temperature
- 20°C / + 45°C



A4159.19.120.927.IP20.DALI

Power & number leds/m
19 w/m & 120 leds/m

CCT & luminous flux/m

	19w/m	
1800K	2650 lm	918
2100K	2680 lm	921
2400K	2700 lm	924
2700K	2717 lm	927
3000K	2736 lm	930
3500K	2831 lm	935
4000K	2888 lm	940
5000K	2875 lm	950
6000K	2869 lm	960

IP Rating

IP20
IP54 (Wet indoor)
IP65H (Semi outdoor)
Pour des IP supérieur, veuillez nous consulter
For higher IP ratings, please contact us.

Dimming

No dimming
Dali
Dmx
Dimming 0/1-10V
Casambi

19.120

IP20
IP54
IP65H

HF
DALI
DMX
DI0
CSB