



DRAGO is a rectilinear illuminating bollard designed for pathways, public parks, and campuses. Featuring fully shielded, Dark Sky-compliant optics, DRAGO offers unique distribution types that enable industry-leading spacing. DRAGO is available in two standard heights, with custom height options providing additional design flexibility. It can also be equipped with chemical anchors, allowing ease of installation while ensuring durability. Additional features include GFCI receptacle, motion sensor, and marine-grade coating.

Product code	Product name	Light distribution	Luminaire luminous flux	Rated input power	Colour temperature	Control	Weight
LB6048.575-EN	DRAGO Forward	[SLF] 65x70°,	774 - 1646 lm	10 - 20 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.575-EN-WO	DRAGO Wood Forward	[SLF] 65x70°,	774 - 1646 lm	10 - 20 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.585-EN	DRAGO Side	[SLS] 145x45°,	307 - 791 lm	5 - 10 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.585-EN-WO	DRAGO Wood Side	[SLS] 145x45°,	307 - 791 lm	5 - 10 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.910-EN	DRAGO 8 LED	[T3-FG] 132x64°, [T3] 150x60°,	642 - 1779 lm	10 - 20 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6048.910-EN-WO	DRAGO Wood 8 LED	[T3-FG] 132x64°, [T3] 150x60°,	642 - 1779 lm	10 - 20 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	3.53 kg (0.25 m), 4.5 kg (0.8 m)
LB6068.570-EN	DRAGO Forward Duo	[SLF] 65x70°,	1548 - 3292 lm	20 - 40 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	4.11 kg (0.25 m), 5.67 kg (0.8 m)
LB6068.571-EN	DRAGO Side Duo	[SLS] 145x45°,	614 - 1582 lm	10 - 20 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	4.11 kg (0.25 m), 5.67 kg (0.8 m)
LB7035.575-EN	DRAGO Ex Forward	[SLF] 65x70°,	774 - 1646 lm	10 - 20 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	4.50 kg (0.35 m), 6.0 kg (0.8 m)
LB7035.585-EN	DRAGO Ex Side	[SLS] 145x45°,	307 - 791 lm	5 - 10 W	2700 K CRI 80, 3000 K CRI 80, 4000 K CRI 80	On/Off, DALI	4.50 kg (0.35 m), 6.0 kg (0.8 m)

Extras


Connectivity



MS

Motion sensor

Consult the factory



EK

Emergency kit

Consult the factory



UNI

120-277V 50/60Hz

Luminaire body options




DPC

Double powder
coating

Accessories (To be ordered separately)

Anchorage



6281000

6281000



[SLF]

Special linear,
Forward throw



[SLS]

Special linear,
Side throw




[T3-FG]

Type III,
Asymmetric,
Side throw -
Frosted Glass




[T3]

Type III,
Asymmetric,
Side throw




[HM1]

Black




[HM2]

Dark grey




[HM3]

Anthracite
grey




[HM4]

Light grey



[HM5]

White



[HM6]

Bronze




[CC]

Custom
colour
(Please
specify RAL
code)



[WLAS]

Wood-Look:
Alpine
Spruce




[WLBf]

Wood-Look:
Brown Fir



[WLRM]

Wood-Look:
Red
Mahogany



[WLSO]


Wood-Look:
Sienna Oak

HEPER HQ - HPR Pazarlama A.Ş.
Başkent OSB 22. Cd. No: 2,
Malıköy, Temelli, Sincan, 06909
Ankara, Turkey
+90 312 267 54 30
info@hepergroup.com


HEPER Europe GmbH
Ahornweg 5a, 58675
Hemer, Germany
+49 2372 568 7570
infoEU@hepergroup.com
www.heperlighting.com/de

We reserve the right to change specifications without prior written notice. Edition: 24.12.2025. For current version visit heperlighting.com. All flux ($\pm 7\%$ tolerance) and power values ($\pm 10\%$ tolerance) are derived following appropriate IES, CIE, and applicable standards.


LB6048.575-EN




LB6048.575-EN-WO




LB6048.585-EN




LB6048.585-EN-WO




LB6048.910-EN




LB6048.910-EN-WO




LB6068.570-EN



LB6068.571-EN



LB7035.575-EN



LB7035.585-EN

