

new

STRATAS.NV80s



scale 1:2

NV80s

1000 lm
Ø 80 mm
narrow
XIM 9 mm LES

Xicato XIM LED (CRI = 98)
narrow spotlight with 48V track with bluetooth (BLE) and
dalicontrol and 0-10V

luminaire

- small construction-kit spotlight system Ø 80mm, with short luminaire body, for 48V track

lamp

- Xicato XIM-Artist
Xicato - module LES 9mm
(CRI = 98), 1000lm, typ. 22W
- colour temperature: 3000 K (2700 K, 3500 K, 4000 K on request)
1x2 step MacAdam initial.
- life hours: 50,000 h – L70/B0/F0
- Colour and lumen consistent over life
- other Xicato-LEDs on request

beam angle

- 2 optics:
narrow spot 11° / spot 15° (with honey comb)

accessoires

- tube
- sculpture lens

control

- Bluetooth low Energie (BLE)
(integrated XIM-module for DALI and 0-10V)

mounting

- track adapter 48V DALI / EUTRAC
- surface mount

orientation


- 0°- 90° vertical tilt and 360° rotation.

material / colour

- aluminium, powder coated
- white, silver, black (other colours available on request)

miscellaneous

- system typ. 22W
- Operating temperature: -25°C to 35°C
- weight: 0,6 kg



STRATAS.NV80s



Maßstab 1:2

NV80s

1000 lm
Ø 80 mm
narrow
XiM 9 mm LES

Xicato XIM LED (CRI = 98)

Strahler für 48V Stromschiene mit bluetooth (BLE) und DALI und 0-10V

Leuchte

- Baukasten-Systemstrahler Ø 80mm, mit kurzem Leuchtenkopf für 48V Stromschiene

Lampe

- XICATO / XIM-Artist
Xicato Modul LES 9mm
(CRI = 98), 1000lm, typ. 22W
- Lichtfarbe: 3000 K (2700 K, 3500 K, 4000 K auf Anfrage)
in 1x2 MacAdam Basis
- Lebensdauer: 50,000 h – L70/B0/F0
- Farbe und Licht konstant während der gesamten Lebensdauer
- andere Xicato-LEDs auf Anfrage

Ausstrahlwinkel

- 2 Optiken:
narrow spot 11° / spot 15° (inkl. Wabenraster)

Zubehör

- Schute
- Skulpturenlinse

Steuerung

- Bluetooth low Energie (BLE)
(XiM-Modul – DALI und 0-10V integriert)

Montage

- Stromschienenadapter 48V DALI / EUTRAC
- Aufbauvariante

Ausrichtung

- 0° - 90° Schwenkbereich und 360° Drehung

Material / Farbe

- Aluminium, pulverbeschichtet
- weiß, silber, schwarz (weitere Farben auf Anfrage)

Sonstiges

- Systemleistung typ. 22W
- Betriebstemperatur -25°C bis 35°C
- Gewicht: 0,6 kg

