


Micro Pendant system

Micro Egg Pendant Miniature 2 Watt LED pendant





Micro Egg LED Pendant

Miniature LED pendant for use with Radiant Micro Track system or with surface mount base

Designed to be used in a wide variety of hospitality and residential applications where the quality and control of light is of high importance.

Product description:

Miniature 2 Watt pendant

Each pendant - 1 x 2 Watt Cree XPE / XBD LED, with lens

Various LED colour temperature and CRI options available

Various TIR optics available

The light output contains very little heat or UV - ideal for the illumination of sensitive materials

Miniature DC to DC dimmable LV constant current driver (up to 700 mA.) housed in the track adapter or surface mount base

12 V DC Supply

Satin black, satin white or any RAL colour finish

| 1 | | , | | | | | | |
|--------------------|-----|-----|-----|--|--|--|--|--|
| 0 | 100 | 200 | 300 | | | | | |
| Lumens per pendant | | | | | | | | |

EN **C €**

| Product Code | IP | Watts per spotlight | Colour Temp. (K) | CRI | Optics | Length of cable (mm) | Mounting Type | Finish | Cable colour |
|----------------------|----|------------------------|---|----------|---|--|------------------|--|---|
| MICRO EGG PENDANT | 20 | 2 | 27=2,700k 30=3,000k 40=4,000k 45=4,500k 50=5,000k | 80 90 | 16° 24° 37° 42° 18+48° 84° | 2mm Ø cable: 100mm - 2000mm 3.5mm Ø cable: 100mm - 6000mm | Surface Track | Black White Any RAL colour Brushed - aluminium Brushed copper | Black White Clear Nickel Other colours available on request |