


Twist Deep Adjustable Round



1177GU53-000000DP10



LIGHT SOURCE:

SYSTEM POWER:

DELIVERED LUMEN: 0Im

SDCM:

CCT:

CRI:

IP.

Notes:

LIGHT SOURCE AND PERFORMANCE

00

0

20

Retrofit - MR16-GU5.3 - Retrofit

00 - No light source

IP20

DESCRIPTION

Ceiling mounted downlight with light body in cast aluminium. Quick and easy installation and relamping via snap-in catch action. Tiltable vertically 0-30° and routable horizontally 350°.

MOUNTING

Indoor Lighting - Surface Mounted

OPTIC

Lens. Narrow, medium and wide beam angle available.

ELECTRICAL / LED DRIVER

DP - Phase

ORDERING CODE

Follow the steps to specify your fixture final code, example: RE61MB13-803020DL11

PRODUCT CODE LIGHT SOURCE CODE - CRI CCT					BEAM ANGLE (BA	\°)	DRIVER OPTIONS FINISH		
1177	GU53	-	00 (00 - No light source	00		DP	10 - Black	
NOTES:									
We reserve the right to change specifications without prior notification.									
HONG KONG	-	LONDON		- MILAN	-	SHANGHAI	-	USA	