


Framing Projector 100



6542BC31-903015D010



DESCRIPTION

Projector with light head and driver box in cast aluminium. Available with 3 circuit universal track adapter or Dali track adapter. Versatile aiming angle tiltable vertically 0°-90° and rotatable horizontally 350°. Framing Projector: polygonal projection. Equipped with 4 shutters to shape and project the light precisely at the desired point. Manual focus adjustment to obtain well defined sharp edges or a shaded effect. Iris Projector: equipped with lenses, snoot and single shutter zoom. Manual focus adjustment to obtain the desired light beam and to well define smaller objects. Gobo Projector: the incorporated lens with snoot allow to project the inserted image/logo. Manual focus adjustment to obtain a well defined image onto a desired surface.

MOUNTING

Indoor Lighting - Track

OPTIC

Lenses. Narrow and medium zoom optics included. single shutter zoom included.

ELECTRICAL / LED DRIVER

D0 - No Dimming

ORDERING CODE Follow the steps to specify your fixture final code, example: RE61MB13-803020DL11

PRODUCT CODE LIGHT SOURCE CODE CRI CCT BEAM ANGLE (BA°) DRIVER OPTIONS FINISH 6542 BC31 90 30 - 3000K 15 D0 10 - Black NOTES: We reserve the right to change specifications without prior notification. HONG KONG LONDON MILAN SHANGHAI USA

LIGHT SOURCE AND PERFORMANCE

LIGHT SOURCE:	LED Built-in with body - Citizen - COB
SDCM:	3-step MacAdam
CCT:	30 - 3000K
CRI:	90
SYSTEM POWER:	15.4
DELIVERED LUMEN:	1122.3lm
IP:	20
Notes:	

