



GENERAL SPECIFICATION

Body: Aluminum.

Finish: Powder coated.

Suspension: Stainless steel cables.

Power cable: Silver braided.

Drivers: HPF electronic drivers for 120-277V (EU-240V), 0-10V, 1% dimming.

Remote Mounting Of Drivers: Wire Size 18 AWG - Max distance (from canopy to drivers) 9.5', Wire size 16 AWG - Max distance 19.5', Wire size 14 AWG - Max distance 29.5'. Drivers must be accessible after installation.

Mechanical: Luminaires attached directly to the J box (by others - North America only).


Diffusers: Frosted acrylic.

L70 @25deg C: > 50,000 hrs.


Delivered Lumens: Delivered lumens & LPW based on 3000K (min 80 CRI) for White LEDs only.

Approvals: Damp Location (Indoor use only).


MOUNTINGS & OPTICS




Interior - Suspended-
Inside/Outside




98 2405




98 2410




98 2420




98 2430




98 2440




98 2450




98 2460




W14




W25




W36




W48



W60



W72



W84

HOW TO ORDER

A SPECIFY LUMINAIRE LENGTH

Code:	Length:	Power (LED):	Delivered lms (Length):	LPW:
98 2410	635mm/25"	27W	3186	120
98 2420	915mm/36"	40W	4780	120
98 2430	1219mm/48"	53W	6372	120
98 2440	1524mm/60"	66W	7966	120
98 2450	1829mm/72"	80W	9558	120
98 2460	2134mm/84"	93W	11152	120

Additional Information

Calculate total lumens by adding the Length lumens to the Width lumens. For example: 36" length x 48" width = 4780 + 6372 = 11152 total lumens.

B SPECIFY WIDTH

Code:	Width:	Power (LED):	Delivered lms (Width):	LPW:
W25	635mm/25"	27W	3186	120
W36	915mm/36"	40W	4780	120
W48	1219mm/48"	53W	6372	120
W60	1524mm/60"	66W	7966	119
W72	1829mm/72"	80W	9558	120
W84	2134mm/84"	93W	11152	120

C SPECIFY CCT/COLOR (OUTSIDE)

T30	3000K (min 80 CRI)
T35	3500K (min 80 CRI)
T40	4000K (min 80 CRI)
TRD	Red
TGN	Green
TBL	Blue

D CCT/COLOR (INSIDE)

S30	3000K (min 80 CRI)
S35	3500K (min 80 CRI)
S40	4000K (min 80 CRI)
SRD	Red
SGN	Green
SBL	Blue

E SPECIFY SUSPENSION

S1	Vertical, Remote Driver
S3	Vertical, Integral Driver

F SPECIFY FINISH

BL	Black
MS	Metallic Silver
WH	White

G SPECIFY LUMEN & WATTAGE REDUCTION

PRO	Lumen & Wattage Reduction to approximately 25% of standard output
PR1	Lumen & Wattage Reduction to approximately 50% of standard output
PR2	Lumen & Wattage Reduction to approximately 75% of standard output

Additional Information


Note: Custom Reduction Percentages Available Upon Request.

EXAMPLE SPECIFICATION CODE



982410/W25/T30/S30/S1/WH

DIMENSIONAL DIAGRAMS

S1 VERTICAL - REMOTE DRIVER



S3 VERTICAL - INTEGRAL DRIVER



APPROVALS

