

Category Interior use only IP20

Material Machined Aluminium

Finish Brushed Aluminium

System Cable System | Basis Track | ReTrac | Eutrac | Monopoint

The Rotor luminaire was designed primarily for the Basis Track system. Gold plated sprung sockets for the lamp pins provide excellent electrical connection, and the innovative lockable design allows for full adjustability. Machined from aluminium, Rotor is available

**Lamp** MR16 [QR-CBC 51] Rating 50W Max at 12V Lockable Pan & Tilt

**Gear Type** Remote

**Accessories** Snoots | Louvres | Lenses


as standard in brushed aluminium.

**Weight** AL - 45g | RB - 115g




68 <del>-</del>25

STANDARD ROTOR



BASIS TRACK ROTOR





Notes



12V



The jack plug system allows the luminaires to be easily removed for

cleaning or relamping. The luminaires click into the jack plug socket, the threaded jacket then screws into position to lock the connection

in place. Once fixed, the luminaires are free to rotate or alternatively,



MPX-138-AL









CA4-138-AL







EUT3-138-AL



MPS-138-AL

50W

MAX

can be secured in place using two locking pins.

For Rotor snoots & accessory holders please see spec sheet 940.

For Rotor accessories please see spec sheet 900. For Rotor XL please see spec sheet 138-400.







MPY-138-AL



MPZ-138-AL





SALES@PRECISIONLIGHTING.CO.UK

LONDON SW17 OBA

42 RIVERSIDE ROAD