THE LUX COMPANY QRP15T









Round Recessed Deep LED Downlight

- · Die cast aluminium housing
- Passive extruded aluminium heatsink
- XTM Xicato remote phosphor LED technology
- Ra81 Standard/Ra81 Vibrant colour rendering up to 1300
 Iumens
- Ra98 Artist/Ra95 Vibrant colour rendering up to 1300 lumens
- · System efficacy up to 129 lm/w


- LED module life rating at 50,000hrs L70/C3
- · 1x2 step MacAdams over life
- · 5 year warranty on LED system
- · Colour consistent over life
- · Concealed fix option
- · Dimming available
- Accessories available (see accessories page)
- · UK design and manufacture

Product Code							
Product	QRP	Round Recessed Deep Downlight					
Reflector Size	15T	50mm Diameter					
	s	Standard Driver					
Drivers	D	Dali Driver					
	В	DSI Driver					
	Α	1-10V Dimming Driver					
	T	Triac Driver					
	04	400 Lumens*					
Lumens	07	700 Lumens					
	10	1000 Lumens					
	13	1300 Lumens					
Colour Temperature	27	2700 Kelvin					
	30	3000 Kelvin					
	35	3500 Kelvin					
	40	4000 Kelvin					
	K	Ra81 Standard					
RA (Colour Rendering)	Α	Ra98 Artist Series					
	V	Ra81 Vibrant					
	R	Ra95 Vibrant					
Beam Angle (9mm LES)	16	16° Twist-lock Reflector					
	24	24° Twist-lock Reflector					
	40	40° Twist-lock Reflector					
Beam Angle (19mm LES)	4T	40° Twist-lock Reflector					
	6T	60° Twist-lock Reflector					
Body Colour	W	White					
	В	Bllack					
	G	Grey					
= 1	0	No Attachment					
	1	3 Hour Emergency Pack					
	2	Self-Test 3 Hour Emergency Pack					
Extras	3	3 Hours Emergency DALI EM Pro					
	5	Concealed Fix					

* Not available with 60° reflector

Colour Rendering Table

		Ra	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
Standard Series	K	81	80	85	89	81	78	80	86	66	16	64	79	58	81	93	75
Artist Series	A	98	98	99	98	98	98	97	98	98	98	99	98	88	98	98	98
Vibrant Series V80	٧	81	81	86	81	81	80	80	85	85	16	66	80	62	82	93	77
Virbant Series V95	R	95	99	98	96	96	98	96	95	95	90	67	95	97	98	98	98





Cut out size: 92mm



Concealed Fix c/w Emergency Pack